

# 300x210mm

**Levelling Gun**

**Trade Levelling Gun**

**Cap**  
1 -5/8" x 5/8" x 3/8"

**Universal curved spacer**  
4 -3/8" x 1/16"

National Customer Service 925-371-7101

**DTA QUALITY TOOLS**

The Choice of Professionals  
[www.dtaigroup.com](http://www.dtaigroup.com)

**Lippage Instructions**

- 1 Place Lippage Spacer between tiles 4" from both ends of the tile.
- 2 Once tile and spacer are in place, fasten the Lippage Cap.
- 3 Clamp the two pieces together with the lippage tool to tighten. This will level & hold the tiles in place while the tile adhesive sets.
- 4 Once tile adhesive has dried, simply kick the Cap along the grout joint to remove.\* Grout to finish tiled area.
- 5 Remove Cap from Spacer for re-use.

\* Refer to adhesive manufacturer for drying time.

- ✓ Holds tiles level
- ✓ Ideal for walls & floors
- ✓ Eliminates lippage on uneven tiles

**Wedge Lippage System**

**DTA Lippage Coverage**

**Products**

250pcs	Wedge spacer x 250pcs	WLS250A
500pcs	Wedge spacer x 500pcs	WLS500A
1000pcs	Wedge spacer x 1000pcs	WLS1000A
2000pcs	Wedge spacer x 2000pcs	WLS2000A
4800pcs	Wedge spacer x 4800pcs	WLS4800A
100 pcs	Wedge cap x 100pcs	WLW100
2000pcs	Wedge cap x 2000pcs	WLW2000A
tool	Wedge levelling tool	WLFT

Tiles often move during the drying process, so to avoid disappointing results and costly repairs use the DTA Lippage System. Using the DTA Lippage System during the installation process will ensure you end up with a lippage free surface.

**DTA Lippage Coverage**

**Square Tiles**

Inch	12"	16"	24"	36"	48"
12"	4 Pcs/FT <sup>2</sup>				
16"	2.3 Pcs/FT <sup>2</sup>				
24"	1 Pcs/FT <sup>2</sup>				
36"			0.7 Pcs/FT <sup>2</sup>		
48"				0.6 Pcs/FT <sup>2</sup>	

**Rectangle Tiles**

Inch	12"	24"	36"	48"
8"	4.5 Pcs/FT <sup>2</sup>			
12"	2 Pcs/FT <sup>2</sup>			
24"		1 Pcs/FT <sup>2</sup>		
36"			0.6 Pcs/FT <sup>2</sup>	

NB: More spacers may be used as required

**DTA QUALITY TOOLS**

The Choice of Professionals  
[www.dtaigroup.com](http://www.dtaigroup.com)

1/2" Maximum tile height  
1/8" Minimum tile height  
1/16" Grout joint  
1/2" Maximum tile height  
1/8" Minimum tile height